

ZHONG SHAN RUI XIAN ELECTRONICS

Add: No. 73, Jinyi Road, Dongfeng Town, Zhongshan City Tel: +86-760-86172690 23935789
 Fax: +86-760-22635327 Http: www.neon-elwire.com E-mail: open686@vip.sina.com

Product Data Sheet

P/N: LED STRIP LIGHT Model: RX-FPC

Description: RX-FPC flexible LED strip light can save 70% electricity energy, and it has long life span. can be applied to any accessible surface.

Features:

1. High quality LED
2. Energy saving
3. Can be cut each 3LEDs (RX-FPC15-5H=2LEDs)
4. Waterproof: IP65
5. Not break up
6. No RF interference
7. Small size and can be bended randomly.
8. Long lifespan: ≥ 20000 hrs.

Applications:

1. Home decorations
2. Car motorcycle bicycle decorations Lighting
3. Advertising signboard
4. Contour sign
5. Party and event centerpiece.
6. Emergency exit;
7. Stairway、 Archway
8. Do it yourself.

Electronical Specifications:

Input Voltage: 12VDC Power: 0.068W/LED
 Single LED viewing angle:
 120°/SMD3528 LED 110°/SMD5050 LED
 30°/3mm round LED 120°/5mm straw hat LED
 20°/5mm round LED 60°/5mm white diffused LED
 Colors available : red, yellow, blue, green, purple, pink,
 white and RGB

Mechanical Specifications:

Dimensions (W x H): --
 Weight: --
 LEDs Space: --
 Length: 24cm, 48cm, etc, Max length up to 500cm
 Operating Temperature: -30°C ~ 60°C
 Storage Temperature: -30°C ~ 65°C
 Bending Diameter: at least 4 times the strip width
 Twisting Angle: 120 degrees per 24cm
 Stretching Force: 0.5kg

※DC12V, the red side-line is the anode.

